



# VT 25 CU *control unit* brochure



## VT 25 CU control unit for DEKRA VT 25 camera series

Small, compact control unit for VT 25 camera series

### Applications

- ▶ Intended for the control of VT 25 camera series

### Features

- ▶ Operation of the camera functions directly at the control unit
- ▶ Integrated data display system (optional)
- ▶ Easy handling
- ▶ Small sized and compact dimensions
- ▶ Additional devices such as monitor and recorder can be connected to the video outputs of the control unit

## Technical specifications - VT 25 CU control unit

This document is for general information only, please consult the system manual for detailed specifications

Housing	robust ABS
Dimension	174x83x225 mm
Weight	1.2 kg
Video output	Y/C out, CVBS
Connections	camera, keyboard, video
Power consumption	30 W
Input voltage	85-264 V AC / 47-440 Hz
Operating temperature	---
Recording	n/a
Monitor	n/a
Resolution	---
Brightness	---
Contrast	---
Reaction time	---
Optionals	monitor, keyboard
Features	---



**DEKRA Visatec GmbH**  
Gewerbepark 7, 87477 Sulzberg/See  
Germany  
Tel. + 49.8376.9215 0  
info.dvg@dekra.com

[www.dekra-visatec.com](http://www.dekra-visatec.com)

